

CLAIMS

What is claimed is:

1. An optical add/drop patch cord comprising:
 - an optical add/drop component disposed in a casing;
 - an input fiber permanently coupled to the casing and optically coupled to the optical add/drop component;
 - a drop fiber permanently coupled to the casing and optically coupled to the optical add/drop component;
 - an add fiber permanently coupled to the casing and optically coupled to the optical add/drop component; and
 - an output fiber permanently coupled to the casing and optically coupled to the optical add/drop component.

2. The optical add/drop patch cord of claim 1, the optical add/drop component comprising:

- an optical substrate;
- a first thin film formed on a first end of the optical substrate;
- a second thin film formed on a second end that opposes the first end; and
- wherein the first thin film is configured to allow at least one wavelength of an optical signal from the input fiber to pass through the first thin film towards the drop fiber while reflecting other wavelength(s) of the optical signal to the second thin film; and
- the second thin film is configured to reflect the other wavelength(s) of the optical signal towards the output fiber while allowing at least one

wavelength to pass through the thin film from the add fiber towards the output fiber.

3. The optical add/drop patch cord of claim 2, the optical substrate comprising:

a first cube having a first attachment face; and

a second cube having a second attachment face that is adhered to the first face when pressed together.

4. The optical add/drop patch cord of claim 1, wherein the input, drop, add and output fibers are coupled to the casing using solder ferrules.

5. The optical add/drop patch cord of claim 1, comprising more than four ports configured to add/drop a plurality of signals.

6. The optical add/drop patch cord of claim 1, the optical add/drop component including the collimating elements for ensuring that light is not dispersed within the optical add/drop component.

7. The optical add/drop patch cord of claim 2, the optical substrate including a combination of glass and air.

8. An optical add/drop patch cord comprising:
- an optical add/drop component disposed in a casing, the optical add/drop component comprising:
 - an optical substrate;
 - a first thin film formed on a first end of the optical substrate; and
 - a second thin film formed on a second end such that the second thin film is opposed to the first thin film;
 - an input port optically coupled to the optical substrate and arranged to propagate a multiplexed optical signal towards the first thin film;
 - a drop port optically coupled to the first thin film and arranged to receive at least one wavelength of the multiplexed signal from the first thin film;
 - an add port coupled to the second thin film and arranged to allow at least one wavelength to pass through the add port and into the second thin film; and
 - an output port coupled to the optical substrate configured to receive signals from the second thin film.
9. The optical add/drop patch cord of claim 8, further comprising:
- an input fiber permanently coupled to the input port and optically coupled to the optical add/drop component;
 - a drop fiber permanently coupled to the output port and optically coupled to the optical add/drop component;
 - an add fiber permanently coupled to the add port and optically coupled to the optical add/drop component; and

an output fiber permanently coupled to the output port and optically coupled to the optical add/drop component.

10. The optical add/drop patch cord of claim 8, further comprising:

an input fiber detachably coupled to the input port and optically coupled to the optical add/drop component;

a drop fiber detachably coupled to the output port and optically coupled to the optical add/drop component;

an add fiber detachably coupled to the add port and optically coupled to the optical add/drop component; and

an output fiber detachably coupled to the output port and optically coupled to the optical add/drop component.

11. The optical add/drop patch cord of claim 8, further wherein the input port, output port, add port and drop port each comprise a solder ferrule.

12. The optical add/drop patch cord of claim 8 wherein:

the first thin film is configured to allow at least one wavelength of an optical signal from the input fiber to pass through the first thin film towards the drop port while reflecting other wavelength(s) of the optical signal to the second thin film; and

the second thin film is configured to reflect the other wavelength(s) of the optical signal towards the output port while allowing at least one wavelength to pass through the thin film from the add port towards the output port.

13. The optical add/drop patch cord of claim 8, comprising more than four ports configured to add/drop a plurality of signals.

WORKMAN NYDEGGER
A PROFESSIONAL CORPORATION
ATTORNEYS AT LAW
1000 EAGLE GATE TOWER
60 EAST SOUTH TEMPLE
SALT LAKE CITY, UTAH 84111

14. A method for manufacturing an optical add/drop patch cord comprising:
enclosing an optical add/drop component in a casing, the optical
add/drop component comprising:

an optical substrate;

a first thin film formed on one end of the substrate; and

a second thin film formed on an end opposing the one end such

that the second thin film is opposed to the first thin film;

optically coupling an input port to the optical substrate whereby a signal
input at the input port will travel towards the first thin film;

optically coupling a drop port to the optical substrate at the first thin film
whereby a signal passing through the first thin film will propagate through the
drop port and a signal reflected by the first thin film will be reflected towards
the second thin film;

optically coupling an add port to the optical substrate at the second thin
film whereby the second thin film is configured to reflect the signals reflected
by the first thin film towards an output port and to permit a signal received by
the add port to pass through the second thin film towards the output port; and

optically coupling the output port to the optical substrate.

15. The method of claim 14, further comprising soldering a fiber to at least
one of the input port, the drop port, the add port, and the output port.

16. The method of claim 14, further comprising constructing the add/drop
module wherein constructing comprises:

arranging two thin film cubes having thin film substrates such that the thin films are diagonally opposed to each other; and

pressing the two thin film cubes together to cause the two thin film cubes to fuse.

17. The method of claim 16, further comprising polishing attachment faces on the thin film cubes where the two thin film cubes will be fused to remove irregularities and impurities.

18. The method of claim 14, comprising forming at least one of the first thin film and the second thin film on the optical substrate forming comprising vapor deposition.

19. The method of claim 14, comprising forming at least one of the first thin film and the second thin film on the optical substrate forming comprising a film growth process.

20. The method of claim 14, further comprising detachably attaching optical fibers to at least one of the input fiber, the drop fiber, the add fiber, and the drop fiber.

21. The method of claim 14, further comprising permanently attaching optical fibers to at least one of the input fiber, the drop fiber, the add fiber, and the drop fiber.

22. An optical patch cord comprising:
- a plurality of optical fibers ;
 - a casing that connects with the plurality of optical fibers using an add port, a drop port, an input port, and an output port;
 - an optical component disposed in the casing, the optical component comprising:

- a first cube that receives an optical signal through the input port, the first cube having a first thin film formed on a face of the first cube, the first thin film configured to drop at least one wavelength of the optical signal through the drop port by allowing the at least one wavelength to pass through the first thin film to the drop port while reflecting other wavelengths of the optical signal; and

- a second cube having an attachment face that adheres to an attachment face of the first cube and having a second film formed on a face of the second cube, the second cube configured to add the at least one wavelength to the optical signal by receiving the at least one wavelength from the add port and passing the at least one wavelength through the second thin film such that the at least one wavelength is added to the other wavelengths which are received from the first thin film and reflected towards the output port.

23. The optical add/drop patch cord of claim 22, wherein the plurality of fibers are connected to the casing by at least one of a molded strain relief, solder, and epoxy.